

## VI.3.6B-SETUP-TEXT PROGRAM PROGDEN SETUP MENU FOR TEXT PARAMATERS

The Setup Menu for Text is used to process Text parameters.

An example of the menu is:

```
Text Identifiers
1) FFGHD   2) FFHHD   3) CWAATL   4)CWABHM   5) CWABNA
6) CWAFTW  7) CWAGSP  8) CWAJAN
Select (a-add c-change d-delete l-list m-more p-previous):
Enter id:
```

### Selection a-add or c-change

For selection 'a' or 'c' a prompt appears for the input source:

Enter parameters (f-file [t]-terminal m-menu):

#### **Selection f-file input**

This selection prompts for directory and filename of an ASCII file containing the parameters. The input data is described in Section VI.3.6C-INFILE-TEXT.

#### **Selection t-terminal input**

This selection prompts for an identifier:

Enter Text ID:

After entering an identifier from the list, the edit screen is displayed.

```
Edit Text Parameters - FFGHD
Lines of text are: 9
1) COUNTY Flash Flood Guidance
2) National Weather Service
3) Arkansas Red Basin River Forecast Center...Tulsa OK
4) ISSUED
5) (blank line)
6) DOTB TUR
7) : Average rainfall in inches needed to begin flooding
8) : ID 1HR 3HR 6HR Name
9) :-----
Enter line # (0-exit):
```

Selecting a number prompts for entering information for the selected line.

Entering 0 (zero) returns to the Text Identifiers menu.

Entering a line number and then the word 'skip' at the beginning of the line creates a blank line.

After selecting a-add, c-change or d-delete, prompts appear for an identifier number and identifier:

```
Enter (number):  
Enter identifier:
```

Selection 'a' moves current identifiers and inserts a new product identifier at the designated number. Selection 'c' replaces the current identifier at number with the new identifier. Selection 'd' removes the desired identifier at number by compressing the identifiers.

### Selection d-delete

This selection displays the following prompt:

```
Delete number:  
Identifier:  
Are you sure (y or n):
```

By responding with the desired identifier number from the identifier list and the corresponding identifier, parameters for the identifier will be deleted and the index compressed. A response of 'n' will abort the deletion process and return to the identifier list.

### Selection l-list

This selection displays the following prompt to write parameters to an ASCII file:

```
Directory and name of output file (<return>-exit)  
Enter:
```

After entering the complete directory and filename, prompts appear for a range of identifier numbers from the identifier list:

```
List from ( 1):  
to (nnn):
```

where nnn is the number of identifiers defined

Parameters for the beginning identifier number through the ending identifier number are written to the specified file. The file can be edited and read as an input file when selection a-add or c-change is selected followed by selection f-file.

### Selection m-more

This selection displays the next screen of identifiers when more identifiers exist beyond the current display.

Selection p-previous

This selection displays the previous screen of identifiers when more than 100 identifiers exist and the first identifier displayed is not identifier labeled 1).